



TECHNICAL DATA SHEET

Type GPC 220 Lubricant

WATER SOLUBLE HIGH TEMPERATURE CONVEYOR LUBRICANT

Mighty Lube Type GPC Lubricant is a pure synthetic, water soluble high temperature conveyor lubricant specially formulated for the lubrication of chains, rollers and bearings of automotive paint line conveyors and other mechanical systems where water solubility and paint compatibility are essential. This product contains no silicone and will not adversely affect paint finishes.

FEATURES:

- Readily dissolves in water and water-based rinses and paints.
- Inhibits rust, corrosion and oxidation.
- Excellent thermal stability.
- Extreme resistance to high temperature oxidation.
- Compatible with all automotive paints and coatings.

TYPICAL SPECIFICATIONS

ISO Grade	220
Specific Gravity:	1.05
Viscosity @ 40°C, cSt (ASTM D445)	220
Viscosity @ 100°C, cSt (ASTM D445)	33
Viscosity Index (ASTM D2270)	195
Pour Point °F (°C) (ASTM D97)	-25 (-32)
Flash Point °F (°C) (ASTM D92)	460 (238)
Copper Corrosion (ASTM D4048)	1B
Rust Test, A & B (ASTM D665)	Pass

AVAILABLE IN 5 GALLON PAILS, 55 GALLON DRUMS

DISCLAIMER:

Since we are unable to anticipate or control the conditions under which this information and our products may be used, we cannot guarantee the applicability of this information or suitability of our products in any specific application. Moreover, the products are sold without warranty, expressed or implied. Statements concerning the possible use of our products are not intended as recommendations to use our product in the infringement of any patent.

REV. 01/11/2019