



TECHNICAL DATA SHEET

Type CSM-2 Lubricant

Mighty Lube Type CSM-2 Lubricant is a heavy duty, anti-wear lubricant, which have been formulated to withstand the most extreme industrial conveyor applications.

The use of the Mighty Lube Systematic Lubrication will result in a conveyor system that is protected against wear and corrosion over temperature ranges of 450°F with limited protection up to 1250°F.

Mighty Lube Type CSM-2 Lubricant is formulated with specialty chemicals to exceed the characteristics of an excellent lubricant. Type CSM-2 Lubricant consist of a solvent which acts as a carrier, cleaner and penetrant providing a pathway for the other components to work their way into the wear points. Graphite and synthetic fluids act as the base for the lubricant. This provides a thin film with anti-wear, extreme pressure and temperature protection.

Mighty Lube Type CSM-2 Lubricant and Mighty Lube Lubricating Equipment are the result of years of development dedicated to providing the industry with the highest quality systematic approach to protection against conveyor wear, corrosion, waste and downtime.

TYPICAL SPECIFICATIONS

Viscosity SUS @ 100° F	45
Pour Point °F	-55° F
Flash Point °F	230° F
Color	Dark Gray
Viscosity Index	140
Solids Lubricant (<i>suspension</i>)	Colloidal Graphite
Rust Preventive Properties (<i>ASTM D665A</i>)	No Corrosion

DISCLAIMER:

Since we are unable to anticipate or control the conditions under which this information and our products may be used, we cannot guarantee the applicability of this information or suitability of our products in any specific application. Moreover, the products are sold without warranty, expressed or implied. Statements concerning the possible use of our products are not intended as recommendations to use our product in the infringement of any patent.